

# vebrobound Stone Carpet



A watertight resin bound aggregate flooring system designed for use in indoor applications, such as pool surrounds and spa facilities.

## why choose **vebrobound** Stone Carpet?



Aesthetically pleasing with design flexibility; can be installed in a variety of colours and patterns



Available in a wide range of natural coloured stone aggregates and blends



Water tight to ensure substrate integrity, even when installed in wet indoor areas



Anti-slip finish, helping to minimise the risk of slips and trips – even in wet conditions



Easy to clean, preserving aesthetic appeal and safety over time



Lifespan in excess of two decades when correctly maintained

## system design & typical properties

(Stone Carpet Specification: 8.0 – 12.0 mm)

### 1 Primer

Specified for use on concrete substrates prior to laying **vebrobound** Stone Carpet.

<b>vebro</b> EP Primer	0.50 kg/m <sup>2</sup>
<b>vebro</b> Natural Quartz 0.3 – 0.8 mm	2.00 kg/m <sup>2</sup>

### 2 Resin Bound Mix Design

<b>vebro</b> PU UV Binder	7.5 kg
<b>vebro</b> Decorative Stone* (2.0 – 5.0 mm)	75.0 kg
<b>vebro</b> Decorative Stone* (1.0 – 3.0 mm)	25.0 kg
<b>vebro</b> 52 Sand	6.0 kg

\*Only mix with suitable washed & kiln dried aggregates no larger than 6.0 mm diameter.

### 3 Pore Sealer

<b>vebro</b> PU Pore Filler (Clear Gloss)	~ 1.00 kg/m <sup>2</sup>
---	--------------------------

### Coverage

A full mix as above will cover ~6.00 square metres at 10.0 mm

### Application Suitability

**vebrobound** Stone Carpet is designed for indoor use only. For external walkways traffic see **vebrobound** Pedestrian.

## contact the **vebro** team

**w:** [vebropolymers.com](http://vebropolymers.com) | **e:** [hello@vebropolymers.com](mailto:hello@vebropolymers.com) | **t:** +44 (0) 1618 738 396

For a full technical profile, please refer to the data sheet for each product in the system design.



[EN-UK] 12/06/25